



# BUMPER COLOR

**D12**VERSION: 170704  
Page: 1/3

## PLASTIC COVERING

### DEFINITION

**BUMPER COLOR** is a flexible coating suitable for bodywork, especially for bumpers. BUMPER COLOR is an all-purpose product for it can be used either to get a good finish in plastics, or as a primer when they have to be painted.



When using it as a finish product, it gives a texture and appearance very similar to new bumpers. We can get different textures by adjusting the nozzle of the spray gun, its pressure and the distance from where the product is applied. Although BUMPER COLOR is a ready to use product, it can be necessary to add a nitro thinner to adjust the texture.

BUMPER COLOR has excellent adhesion, and can be used as a primer for the repairing of bumpers that need to be painted, as well as a basis to increase the adhesion of polyester putties on plastic. In this case, to get a flat finish the product will have to be diluted with SO72.

### PHYSICAL CHARACTERISTICS

|                            |   |
|----------------------------|---|
| <b>Nature:</b>             | Acrylic resins  |
| <b>Color:</b>              | Black, grey anthracite, white                                     |
| <b>Aspect:</b>             | Satin   |
| <b>Specific weight:</b>    | 1,1 kg/l at 20°C Black, grey anthracite<br>1,2 kg/l at 20°C White |
| <b>Dry film thickness:</b> | 80-100 microns 2 coats  |
| <b>Yield:</b>              | 5-6 m <sup>2</sup> /l   |
| <b>VOC:</b>                | 506 g/l Black, grey anthracite<br>496 g/l White                   |
| <b>Solid content:</b>      | 56 % Black, grey anthracite<br>59 % White                         |







### SURFACE PREPARATION

| PROCESS   |                  | Paint OEM | Putty | Plastics |
|---|------------------|-----------|-------|----------|
|  | HIGHER THAN P240 | ✓         | ✓     | ✓        |
|  | DA93             | ✓         | ✓     | ✓        |

### MIXING RATIO

| BUMPER COLOR | A + C   | Texturized finish |
|--------------|---------|-------------------|
| SO72         | 0 %     | Coarse            |
|              | 10-20 % | Fine              |
|              | 40 %    | Primer            |

### APPLICATION METHOD

|   |  mm |  bar |  cm |  |  |
|---|--|--|--|---|---|
|  | 1.7-1.9  | 3-3.5  | 15 - 20  | 1-2   | 5'  |

### EQUIPMENT CLEANING

Clean with a cleaning thinner.

### SAFETY

Follow instructions of product label. For more information check the Material Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

### STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

### SHELF LIFE

One year in unopened original packaging.

#### SUGGESTION:

It is recommended to use this product as a sanding guide in black bumpers diluted to 100%.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.