



CAVITEX

D9VERSION: 121212
Page:1/1

CAVITIES WAX

DEFINITION

CAVITEX is a specially designed wax for the protection of bodywork empty spaces such as underbodies, interior doors, wings...





It forms a protector film, it is water repellent, flexible and adherence to a wide range of temperatures. It offers good resistance to abrasion, humidity and detergents usually used in industry.

The solvent used in the formulation of this wax do not attack the support of paint.

PHYSICAL CHARACTERISTICS

Nature:	Waxes and antioxidants		
Colour:	Beige translucent		
Specific weight:	0,9 kg/l at 20°C		
Solids content:	42 %		
VOC:	522 g/l	2004/42/EC - IIB(e)(840)(522)	

APPLICATION METHOD

			
Shake before use	RB1	3-4 kg/cm ²	1

REMARKS

Shake before use. Apply the product with extendable tubes for difficult to access areas.

EQUIPMENT CLEANING

Clean with a cleaning thinner.

SAFETY

Follow instructions of product label. For more information check the Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.