



AIRCOLOR GUIDEX

H11VERSION: 170607
Page:1/2

SANDING GUIDE COATING

DEFINITION






AIRCOLOR GUIDEX is a black spray product that can be applied on the repair area before sanding and that once sanded shows all the imperfections of the surface being worked on.

It is a fast and clean product that does not need to dry. It also has an advantage cost-wise as it is an aerosol, so no preparation of cleaning or tools is required, which means time saved for the person applying it.

PHYSICAL CHARACTERISTICS

Nature:	Nitrosynthetic
Propellant:	DME
Colour:	Black
Specific Weight:	0,8 Kg/ a 20°C
Extrusion Speed:	1,4 ± 0,4 g/s
Aerosol Pressure:	4,9 ± 0,5 bar a 25°C
Yield:	15-20 m ² /spray
Temperature resistance:	< 50 °C
VOC:	690 g/l Application 2004/42/EC - IIB (e)(840)


APPLICATION METHOD

		 cm		
Nozzle kind: Pocket Black / White	1	30	1	5'

OBSERVATIONS

Shake the aerosol before use for 1 minute after hearing the steel mixing balls move.
Protect the areas that will not be painted.

EQUIPMENT CLEANING



SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

SHELF LIFE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.