



# SILTEX 800

**D1**VERSION: 121212  
Page: 1/2

## PREMIUM HS STONE CHIP

### DEFINITION

HS Stone chip protector of high performance suitable for applications over visible, as well as non visible parts of bodyworks which require reproducing the quality level of the original application.






Its formulation provides a great flexibility level, what makes it perfect for anticorrosive protection and protection against impacts in parts as underbodies and wheel wells. Besides, guarantees an optimal soundproofing in applications over parts with a high level of vibrations as doors, boots, or panels.

Once dry, the excellent texture created in the finish of **SILTEX 800**, allows it to be painted with bodywork basecoat paints, achieving a perfect gloss level.




### PHYSICAL CHARACTERISTICS

<b>Nature:</b>	Elastomers and synthetic resins
<b>Colour:</b>	Grey, black, white
<b>Specific weight:</b>	1,5 kg/l at 20°C
<b>Dry film thickness:</b>	150-200 microns 1 coat
<b>Yield:</b>	5-7 m <sup>2</sup> /Kg
<b>VOC:</b>	410 g/l
<b>Solid content:</b>	72 %

### METHOD OF APPLICATION

				
Shake before using	RB1 schutz gun	3-4 kg/cm <sup>2</sup>	15-25	1-2
	HP cannister gun	2 kg/cm <sup>2</sup>		

### DRYING TIMES

		
10°C	2h	90'
20°C	1,5h	60'
30°C	1h	45'

### REMARKS

The product is ready to use and it does not require additional thinner.  
Shake before using.  
Apply to grease and rust-free surfaces.  
Avoid any mechanical action against the treated parts before 24 hours (for example: car wash with high pressure hot water).  
The product can be over-painted at 30'-40', only if the paint is dried at ambient temperature.

### EQUIPMENT CLEANING

Clean the equipment with a cleaning thinner before the pot life has expired.

### SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

### STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

### GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department.  
ROBERLO SA declines any responsibility due to an incorrect use of the product.