



# PREFILL WB

**H22**VERSION: 130325  
Page:1/2

## REFILLABLE AEROSOL

### DEFINITION

**AIRCOLOR PREFILL WB** is a refillable aerosol for water-based paint with good opacity. Pre-filled with 300ml propellant, solvent and additives, it has the capacity for 100ml of undiluted **OPABASE ACQUA**, this is filled with an aerosol filling machine which produces a ready to use product. Slight colour differences may occur. Always check the colour before application. It can be applied either for spot repairs or refinishing parts.





It is recommended to use it within a maximum of 1 week.

**AIRCOLOR PREFILL WB** has a transversal nozzle allows the direction of application to be adjusted by the output nozzle (horizontal/vertical).

### PHYSICAL CHARACTERISTICS

<b>Propellant:</b>	DME
<b>Specific weight:</b>	0,74 kg/l at 20°C
<b>Aerosol pressure:</b>	3 bar at 20°C
<b>Yield:</b>	depending on consistence and colour of the substrate
<b>VOC:</b>	<810 g/l Application 2004/42/EC - IIB (e)(840)(<810)


### APPLICATION METHOD

			
Transversal nozzle	2 min	approx. 25 cm	Add 100 ml to the undiluted paint <b>OPABASE ACQUA</b>

### REMARKS

Area must be clean, dry and free of grease and dust.  
Shake the aerosol before use for 2 minutes.  
Protect the areas that will not be painted.  
Carry out test spray.  
Spray several thin coats at the recommended distance.  
Drying time depends on type of paint, film thickness and the temperature.  
In the case of force drying, this can be done with air flow using the correct device.  
Re-coatable with 2k clear coats.

### EQUIPMENT CLEANING



## SAFETY

Follow instructions on the product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

## STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +10°C and +25°C with relative air humidity of maximum 60%. Store free from frost.

## GUARANTEE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department.  
ROBERLO SA declines any responsibility due to an incorrect use of the product.