



AIRCOLOR ACRYLIC PAINT

H33

VERSION: 130325
Page:1/2

ACRYLIC PAINT

DEFINITION



AIRCOLOR ACRYLIC PAINT is a premium acrylic enamel with a satin-finish especially formulated for the quick coating of Industrial surfaces. Thanks to the atomization it can also be used on larger surfaces. An extreme high content of pigments and specific additives provide excellent opacity, high film-thickness, low tendency for runs and good adhesion direct on metal. It can be applied either for spot repairs or refinishing parts.

PHYSICAL CHARACTERISTICS





| | |
|--------------------------------|--|
| Nature: | Acrylic |
| Colour: | Black, white |
| Aspect: | Glossy (Gloss: 80% at 60°) |
| Specific weight: | 0,8 kg/l at 20°C |
| Propellant: | Dimethylether and GLP |
| Aerosol pressure: | 4,5 bar at 20°C |
| Yield: | Depending on consistence and colour of the substrate 400 ml are sufficient for approx.0,8 - 1,0 m ² |
| Temperature resistance: | to 90°C |
| VOC: | <790 g/l |

Application 2004/42/EC - IIB (e)(840)(<790)






SURFACE PREPARATION

| PROCESS | | Paint OEM | Primer |
|---|------|-----------|--------|
|  | P360 | ✓ | ✓ |
|  | DA93 | ✓ | ✓ |

APPLICATION METHOD

| | | | |
|---|---|---|---|
|  |  |  |  |
| 2' | 20-25 cm | 2-3 coats | 5' |

DRYING TIMES

| | | | | |
|---|--|---|---|---|
|  |  |  |  |  |
| 20°C | 10'-15' | 30' | 1h | 15' (*) |

(*) In order to increase the degree of gloss and to enhance the chemical resistance recoat with acrylic lacquer after approx 15 min. flash-off time (20°C) with 1K or 2K Clear.

REMARKS

Shake the aerosol before use for 2 minutes after hearing the sound of steel mixing balls.
Carry out test spray. Check the colour.
Drying time depends on temperature, humidity and film thickness which has been applied.

EQUIPMENT CLEANING



SAFETY

Follow instructions on the product label. For more information check the Safety Data Sheet.
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

GUARANTEE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.