



AIRCOLOR FADE OUT SPRAY

H25VERSION: 130325
Page: 1/2

ADDITIVE FOR FADE-OUT

DEFINITION

AIRCOLOR FADE OUT SPRAY is an additive for fade-out spraying, geared mainly towards the "spot repair" market. Excellent fluidity and ease of application. Allows optimum integration of clear coats/colors to partially painted areas. Saves considerable time in the polishing process.




AIRCOLOR FADE OUT SPRAY has a transversal nozzle allows the direction of application to be adjusted by the output nozzle (horizontal/vertical).

PHYSICAL CHARACTERISTICS

Nature:	Special resin
Colour:	Transparent
Specific weight:	0,8 kg/l at 20°C
Propellant:	Dimethylether
Aerosol pressure:	4 bar at 20°C
Temperature resistance:	to 90°C
VOC:	<820 g/l Application 2004/42/EC - IIB (e)(840)(<820)

APPLICATION METHOD

Shake can briefly and test spray. Apply the **AIRCOLOR FADE OUT SPRAY** directly onto the edge of the area of clearcoat/paint with several thin coats and at a distance of approximately 25 cm from the painted area. After curing, the blended area it can be polished to high gloss.

		
2'	25 cm approx.	2-3 thin coats

EQUIPMENT CLEANING



AIRCOLOR FADE OUT SPRAY

ADDITIVE FOR FADE-OUT

H25

VERSION: 130325
Page: 2/2

SAFETY

Follow instructions on the product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +10°C and +30°C.

GUARANTEE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.