



# ROBFLOW

## A37

VERSION: 150930  
Page: 1/2

### GLAZING PUTTY

#### DEFINITION

**ROBFLOW** is a two-component pourable putty used for final skimming polyester fillers or for direct application on minor imperfections in most vehicle substrates. It fills pinholes and scratches in one coat.

**ROBFLOW** is easy to apply, self-leveling and sands very quickly.

#### PHYSICAL CHARACTERISTICS

<b>Nature:</b>	Unsaturated polyester	
<b>Colour:</b>	Light green	
<b>Specific weight:</b>	1,0 kg/l at 20°C	
<b>VOC:</b>	3 g/l Mixing Application	2004/42/EC - IIB(b)(250) 3g/l

#### AUXILIARY PRODUCTS




Hardener PBO

#### SUITABLE SURFACES




It may be applied on steel, aluminium or polyester surfaces.  
When maximum protection is required apply on epoxy primer.  
Do not apply on thermoplastic finishes and Wash Primers.

#### SURFACE PREPARATION





- 1 - Identify surface.
- 2 - Process:

PROCESS		Steel	Aluminium	Polyester UP-GFK
	P80	✓	✓	✓
	P150	✓	✓	✓
	DA93	✓	✓	✓

### 1 – APPLICATION

	 WEIGHT		
10°C	100:2	9'	30'
20°C		5'	20'
30°C		3'	15'

### 2 – SANDING

		 ORBIT		
	INITIAL ↓ FINAL	7 - 5 mm	P180	P150
		5 - 3 mm		P240

### REMARKS

Do not add more hardener than specified. Mix thoroughly.  
It must be isolated before applying finish coating.  
Polyester putties will not harden at temperatures under +5°C.

### EQUIPMENT CLEANING

Clean putty knives with a cleaning thinner before the product hardens.

### SAFETY

Follow instructions of product label. For more information check the Safety Data Sheets.  
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

### STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

### GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department.  
ROBERLO SA declines any responsibility due to an incorrect use of the product.