

# PUR 888

## DEFINITION

2K anti-slip polyurethane paint. The system provides a rough anti-slip finish very resistant to abrasion.

- The recommended base/binder ratio is 20/80 in weight, except for colours that do not cover well, when 30/70 can be used.

## PHYSICAL CHARACTERISTICS OF THE PAINT










<b>Nature:</b>	2K Polyurethane
<b>Appearance:</b>	Rough
<b>Specific weight:</b>	1,1-1,3 kg/l at 20°C
<b>Solid content:</b>	67-74 % Weight
<b>Solids by volume (binder):</b>	61 ± 2 %
<b>Solids by volume (ready to use):</b>	53 ± 2 % E-9005
<b>VOC ready to use:</b>	< 500 g/l - 2004/42/EC - IIA(j)(500)
<b>Dry film thickness:</b>	60-70 microns (1 coat)
<b>Theoretical yield:</b>	9-10 m <sup>2</sup> /l

## SUBSTRATE AND PREPARATION

**New substrates:** Apply over vinyl, epoxy or polyurethane primers

**Old paints:** Sand and degrease (Orbit P240/400)






## MIXING RATIO AND APPLICATION METHOD

<b>PUR 888 :</b> <b>Hardener</b> <b>E-9005 :</b> <b>Thinner PU74</b> <b>normal</b>					 mm	 bar		
 Aerographic	100:17:5-10 volume	6:1+5-10%	20"-23" F/4 20°C	7-8 h	2,5	1,5 max	1 (*)	10' 20°C

(\*) For colours that do not cover well, it is recommended to apply the same or a similar color with a smooth finish, for example with PUR 800-G.

# PUR 888

## DRYING TIMES

			THROUGH DRY		
20° C	10'-15'	2:45h-3:15h	>5h	60° C	1h

- Maximum physical-chemical resistance is obtained after drying at room temperature for 15 days or 7 days when oven dried.

## REMARKS

The product contains abrasives particles, so it is recommended to use suitable protection during the application.

Recommended to be used in ventilated spray booth at 20°C.

## EQUIPMENT CLEANING

Use a cleaning thinner before the pot life has expired.

## SAFETY

Follow instructions of product label. For more information check the Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

## STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

## SHELF LIFE

In unopened original packaging, one year from manufacturing date.