



AIRCOLOR ACRYLIC PAINT

H37

VERSION: 180528
Page:1/2

ACRYLIC PAINT

DEFINITION

AIRCOLOR ACRYLIC PAINT is a premium acrylic enamel with a satin-finish especially formulated for the quick coating of Industrial surfaces. Thanks to the atomization it can also be used on larger surfaces. An extreme high content of pigments and specific additives provide excellent opacity, high film-thickness, low tendency for runs and good adhesion direct on metal. It can be applied either for spot repairs or refinishing parts.

CARACTERÍSTICAS FÍSICAS

Nature:	Thermoplastic acrylic resin
Propellant:	DME
Colour:	Black, White
Specific weight:	0,8 kg/l a 20°C
Shine (60°C):	>70% Glossy 70-50% Satin <10% Matt
Yield:	2,5 m ² /spray
Dry film thickness:	15 µ/coat
Resistance of the container to heat:	< 50 °C
Resistance of paint to heat:	120°C
VOC:	686 g/l

Application 2004/42/EC - IIB (e)(840)

SURFACE PREPARATION

PROCESS		Paint OEM	Primer
	P360	✓	✓
	DA93	✓	✓

APPLICATION

2'	20-25 cm	2-3 coats	5'

DRYING TIMES

20°C	10'-15'	30'	1h	15' (*)

(*)In order to increase the degree of gloss and to enhance the fuel resistance recoat with acrylic lacquer after approx 15 min. flash-off time (20°C) with 1K Clear.

REMARKS

Shake the aerosol before use for 2 minutes after hearing the sound of steel mixing balls.
Carry out test spray. Check the colour.
Drying time depends on temperature, humidity and film thickness which has been applied.

EQUIPMENT CLEANING**SAFETY**

Follow instructions on the product label. For more information check the Safety Data Sheet.
Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

SHELF LIFE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.