

First edition date: 1-5-2014 Last revision date: 5-5-2014 Number of pages: 1

Technical Data Sheet

General

Article number: 9300

Description: Colad Easy2Check®



Specification

Colad Easy2Check® is used to create a temporary gloss on either spray cards (for color matching) or on car panels for panel checking during the sanding process.

Content: 400ml can

Suitable for: +/- 150 Colad spray sample checks [Colad Spray Samples,

Art.no. 9315] or +/-15 - 20 Panel checks

Features: Odorless

Evaporates completely after use without leaving residue [+/- 15 minutes]

Packing: 12 cans per carton

1200 cans per pallet

Operating instructions

Spray sample color match

Spray on base coat Spray Sample [Art.no.9315] to create a temporary gloss. Match the sample with the car. Advisable is to also spray on the object to get the best effect. Repeat this process until the optimal color has been achieved.

Sanding / Panel Check

To check straightness of a repaired panel during the sanding process. Simply spray on Colad Easy2Check® to create a temporary gloss and examine the panel for any defects.

Remarks

- Decrease the evaporation time by blowing air over the surface
- Can be used in the bodyshop or paintshop
- Safe to spray on cured plastic filler

Note

UV-Blockers in a clear coat can affect the cast of certain colors compared to using Colad Easy2Check®. Advise is to use the appropriate clear coat to confirm for a final check.

Created by:

E.M.M. International BV Marsweg 59 8013 PE Zwolle The Netherlands phone +31 38 4676600 fax +31 38 4676699 www.emm.com

