



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HARDENER POLYESTER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Curing chemical

Recommended restrictions
on use : For use in industrial installations or professional treatment
only.

1.3 Details of the supplier of the safety data sheet

Company : Roberlo s.a.
Ctra. Nacional II, Km. 706,5
17457 Riudellots de la Selva
Spain

Telephone : +34972478060

Telefax : +34972477394

E-mail address of person
responsible for the SDS : msds@roberlo.com

1.4 Emergency telephone number

+34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H242 Heating may cause a fire.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
Prevention:
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
Storage:
P411 + P235 Store at temperatures not exceeding 30°C / 86°F. Keep cool.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
dibenzoyl peroxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Organic Peroxides, Solid

HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
dibenzoyl peroxide	94-36-0 202-327-6 01- 2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 45 - < 52$
ethane-1,2-diol	107-21-1 203-473-3 01- 2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373	$\geq 5 - < 9.9$
oxydipropyl dibenzoate	27138-31-4 248-258-5	Aquatic Chronic 2; H411	$\geq 1 - < 2.5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
If eye irritation persists, consult a specialist.
- Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

If swallowed : Do NOT induce vomiting.
Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Skin contact may provoke the following symptoms:
Redness
Ingestion may provoke the following symptoms:
Local irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Benzoic acid
Benzene
Biphenyls
Phenylbenzoate

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Ventilate the area.

6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in area provided with appropriate exhaust ventilation.
Keep away from heat.
Avoid exceeding the given occupational exposure limits (see section 8).
Avoid contact with skin and eyes.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Avoid shock and friction. Keep away from sources of ignition -
No smoking. Keep away from combustible material.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.

Advice on common storage : Do not store near acids.
Reducing agents
Heavy metals

Storage period : 12 Months

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the use of this product do not exist particular recommendations apart from that already indicated.

HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
ethane-1,2-diol	107-21-1	STEL	40 ppm 104 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
ethane-1,2-diol	107-21-1	TWA	20 ppm 52 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
ethane-1,2-diol	107-21-1	TWA (Vapour)	20 ppm 52 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethane-1,2-diol	107-21-1	TWA (particles)	10 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethane-1,2-diol	107-21-1	STEL (Vapour)	40 ppm 104 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

benzoyl peroxide : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 11.75 mg/m³

ethanediol : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 35 mg/m³

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection

Material : Protective gloves complying with EN 374.
Break through time : > 30 min
Glove thickness : > 0.14 mm
Neoprene gloves
Nitrile rubber

Remarks : Please observe the instructions regarding permeability and



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : red

white

Odour : characteristic

pH : Not applicable

Melting point/range : not determined

Boiling point/boiling range : not determined

Flash point : Not applicable

Upper explosion limit : not determined

Lower explosion limit : not determined

Vapour pressure : not determined

Density : 1.14 - 1.20 g/cm³ (20 °C)
Method: ISO 2811-1

Solubility(ies)
Water solubility : insoluble

Auto-ignition temperature : not determined

Viscosity
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

9.2 Other information

Self-Accelerating decomposition temperature (SADT) : 50 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reducing agents
Heavy metals
Amines
Strong acids

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : Benzoic acid
Benzene
Biphenyls
Phenylbenzoate

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): 7,710 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 24.3 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403

ethane-1,2-diol:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg
Method: OECD Test Guideline 402

oxydipropyl dibenzoate:

Acute oral toxicity : LD50 Oral (Rat): 5,313 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: May cause sensitisation by inhalation and skin contact.

Germ cell mutagenicity

Product:

Germ cell mutagenicity- Assessment : Based on available data, the classification criteria are not met.



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

Carcinogenicity

Product:

Carcinogenicity - Assessment : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibenzoyl peroxide:

Toxicity to fish : LC50 (Fish): 0.06 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0.11 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 0.06 mg/l
Exposure time: 72 h



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

Method: OECD Test Guideline 201

ethane-1,2-diol:

Toxicity to fish : LC50 (Fish): 18,500 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 2,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

SECTION 14: Transport information

14.1 UN number

ADR : 3108
IMDG : 3108
IATA : 3108

14.2 UN proper shipping name

ADR : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
IMDG : ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
IATA : Organic peroxide type E, solid (Dibenzoyl peroxide)

14.3 Transport hazard class(es)

ADR : 5.2
IMDG : 5.2
IATA : 5.2

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
IMDG
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R
IATA
Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

14.5 Environmental hazards

ADR
Environmentally hazardous : yes
IMDG
Marine pollutant : yes

14.6 Special precautions for user

Not applicable



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES	50 t	200 t
E1	ENVIRONMENTAL HAZARDS	100 t	200 t

Other regulations : The product is classified and labelled in accordance with EC directives or respective national laws.

15.2 Chemical Safety Assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H241	Heating may cause a fire or explosion.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



HARDENER POLYESTER

Version 2.0

MSDS Number: S00016

Revision Date: 03.03.2017