



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DICROM DB-524

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Solvent-borne coatings

Recommended restrictions  
on use : For use in industrial installations or professional treatment  
only.

#### 1.3 Details of the supplier of the safety data sheet

Company : Roberlo s.a.  
Ctra. Nacional II, Km. 706,5  
17457 Riudellots de la Selva  
Spain

Telephone : +34972478060

Telefax : +34972477394

E-mail address of person  
responsible for the SDS : msds@roberlo.com

#### 1.4 Emergency telephone number

+34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Specific target organ toxicity - repeated  
exposure, Category 2 H373: May cause damage to organs through pro-  
longed or repeated exposure if inhaled.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-  
posure, Category 3 H335: May cause respiratory irritation.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-  
posure, Category 3 H336: May cause drowsiness or dizziness.

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

posure, Category 3

Chronic aquatic toxicity, Category 3

H412: Harmful to aquatic life with long lasting effects.

### Classification (67/548/EEC, 1999/45/EC)

Flammable

R10: Flammable.

Harmful

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

R67: Vapours may cause drowsiness and dizziness.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

: Warning

Hazard statements

:

H226  
H373

Flammable liquid and vapour.  
May cause damage to organs through prolonged or repeated exposure if inhaled.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Harmful to aquatic life with long lasting effects.

H319  
H335  
H315  
H336  
H412

Precautionary statements

: **Prevention:**

P260  
P260  
P264  
P271  
  
P280  
  
P284

Do not breathe vapours.  
Do not breathe spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.  
In case of inadequate ventilation wear respiratory protection.

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P352 Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

### Disposal:

P273 Avoid release to the environment.

P501a This material and its container must be disposed of in a safe way.

Hazardous components which must be listed on the label:  
xylene (mixture of isomers)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Paint

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
xylene (mixture of isomers)	1330-20-7 215-535-7 01- 2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 25 - < 30
n-butyl acetate	123-86-4 204-658-1 01- 2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 15
Solvent naphtha (petro-	64742-95-6	Flam. Liq. 3; H226	>= 2.5 - < 10

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

leum), light arom.	265-199-0 01- 2119455851-35	Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411	
diacetone alcohol	123-42-2 204-626-7 01- 2119473975-21	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335	$\geq 3 - < 10$
ethylbenzene	100-41-4 202-849-4 01- 2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 1 - < 10$
Substances with a workplace exposure limit :			
1-methoxy-2-propanol	107-98-2 203-539-1 01- 2119457435-35	Flam. Liq. 3; H226	$\geq 10 - < 15$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Dry chemical

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### 6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Avoid formation of aerosol. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : For the use of this product do not exist particular recommendations apart from that already indicated.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene (mixture of isomers)	1330-20-7	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
xylene (mixture of isomers)	1330-20-7	STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
xylene (mixture of isomers)	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
xylene (mixture of isomers)	1330-20-7	STEL	100 ppm 442 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 568 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
1-methoxy-2-propanol	107-98-2	STEL	150 ppm 560 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m3	GB EH40
n-butyl acetate	123-86-4	STEL	200 ppm 966 mg/m3	GB EH40
diacetone alcohol	123-42-2	TWA	50 ppm 241 mg/m3	GB EH40
diacetone alcohol	123-42-2	STEL	75 ppm 362 mg/m3	GB EH40
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
ethylbenzene	100-41-4	STEL	200 ppm 884 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethylbenzene	100-41-4	STEL	125 ppm 552 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

xylene : End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 77 mg/m3

n-butyl acetate : End Use: Workers  
Exposure routes: Inhalation



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

Low boiling point naphtha - unspecified	<p>Potential health effects: Long-term systemic effects Value: 480 mg/m<sup>3</sup></p> <p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 608 mg/m<sup>3</sup></p>
4-hydroxy-4-methylpentan-2-one	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 66.4 mg/m<sup>3</sup></p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 66.4 mg/m<sup>3</sup></p>
ethylbenzene	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 77 mg/m<sup>3</sup></p>
1-methoxy-2-propanol	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 369 mg/m<sup>3</sup></p>

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Remarks : Solvent-resistant gloves The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Before removing gloves clean them with soap and water.

Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: viscous liquid
Colour	: red
Odour	: characteristic



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

pH	: Not applicable
Melting point/range	: not determined
Boiling point/boiling range	: not determined
Flash point	: 29 °C Method: ISO 1523, closed cup Setaflash
Upper explosion limit	: not determined
Lower explosion limit	: not determined
Vapour pressure	: not determined
Density	: 0.987 g/cm <sup>3</sup> (20 °C) Method: ISO 2811-1
Solubility(ies) Water solubility	: not determined
Viscosity Viscosity, dynamic	: 2000 mPa.s (20 °C) Method: ISO 2555
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s (40 °C)

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if used as directed.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents  
Strong acids and strong bases

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon monoxide

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

##### Components:

##### **xylene (mixture of isomers):**

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 22.08 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate : 1,100 mg/kg  
Method: Converted acute toxicity point estimate

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 10,768 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 17,600 mg/kg  
Method: OECD Test Guideline 402

##### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 Oral (Rat): 3,592 mg/kg

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 3,160 mg/kg  
Method: OECD Test Guideline 402

### **diacetone alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 3,002 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 7.6 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 13,750 mg/kg  
Method: OECD Test Guideline 402

### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 17.4 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg  
Method: OECD Test Guideline 402

### **1-methoxy-2-propanol:**

Acute oral toxicity : LD50 Oral (Rat): 4,016 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5,456 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate : 13,000 mg/kg  
Method: Converted acute toxicity point estimate

### **Skin corrosion/irritation**

#### **Product:**

Result: Skin irritation

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Severe eye irritation



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### Respiratory or skin sensitisation

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

**Product:**

Germ cell mutagenicity- Assessment : Based on available data, the classification criteria are not met.

### Carcinogenicity

**Product:**

Carcinogenicity - Assessment : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Product:**

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

### STOT - single exposure

**Product:**

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### STOT - repeated exposure

**Product:**

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### Aspiration toxicity

**Product:**

Based on available data, the classification criteria are not met.

### Further information

**Product:**

Remarks: Solvents may degrease the skin.

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **xylene (mixture of isomers):**

Toxicity to fish : LC50 (Fish): 14 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 16 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): > 10 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

##### **n-butyl acetate:**

Toxicity to fish : LC50 (Fish): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 32 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 675 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

##### **Solvent naphtha (petroleum), light arom.:**

Toxicity to fish : LC50 (Fish): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3.2 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 2.9 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

##### **diacetone alcohol:**

Toxicity to fish : LC50 (Fish): 420 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 1,000 mg/l  
Exposure time: 48 h

## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### ethylbenzene:

Toxicity to fish : LC50 (Fish): 12 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1.8 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 33 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### 1-methoxy-2-propanol:

Toxicity to fish : LC50 (Fish): 20,800 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 23,300 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Algae): 10 mg/l  
Exposure time: 72 h

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic or-



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

ganisms, may cause long-term adverse effects in the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Offer surplus and non-recyclable solutions to a licensed disposal company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14: Transport information

#### 14.1 UN number

- ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

- ADR : PAINT  
IMDG : PAINT  
IATA : Paint

#### 14.3 Transport hazard class(es)

- ADR : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

- ADR  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3
- IMDG  
Packing group : III  
Labels : 3



## DICROM DB-524

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

EmS Code : F-E, S-E

**IATA**

Packing instruction (cargo aircraft) : 366

Packing instruction (LQ) : Y344

Packing group : III

Labels : Flammable Liquids

### 14.5 Environmental hazards

**ADR**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams)	2,500 t	25,000 t

Other regulations : The product is classified and labelled in accordance with EC directives or respective national laws.

### 15.2 Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### Full text of H-Statements

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.



## **DICROM DB-524**

Version 1.0

MSDS Number: H54799

Revision Date: 17.01.2017

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.