

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DICROM DP-902

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Solvent-borne coatings, Base coating

Recommended restrictions on use : For use in industrial installations or professional treatment only.

1.3 Details of the supplier of the safety data sheet

Company : Roberlo s.a.
Ctra. Nacional II, Km. 706,5
17457 Riudellots de la Selva
Spain

Telephone : +34972478060

Telefax : +34972477394

E-mail address of person responsible for the SDS : msds@roberlo.com

1.4 Emergency telephone number

+34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Respiratory system H335: May cause respiratory irritation.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P260 Do not breathe spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

n-butyl acetate
butan-1-ol
Solvent naphtha (petroleum), light arom.
xylene (mixture of isomers)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	$\geq 30 - < 50$
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	$\geq 3 - < 10$
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	$\geq 2.5 - < 10$
xylene (mixture of isomers)	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	$\geq 1 - < 10$
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228 Water-react. 2; H261	$\geq 1 - < 10$
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 1 - < 2.5$
isopropyl alcohol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|-------------------------|---|---|
| General advice | : | Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended. |
| If inhaled | : | Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- | | | |
|--------------------------------------|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Storage period : 12 Months

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the use of this product do not exist particular recommendations apart from that already indicated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
xylene (mixture of isomers)	1330-20-7	TWA	50 ppm 220 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

		STEL	100 ppm 441 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
aluminium powder (stabilised)	7429-90-5	TWA (Inhalable)	10 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable)	4 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

	approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 441 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	125 ppm 552 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
isopropyl alcohol	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40
		STEL	500 ppm 1,250 mg/m3	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	480 mg/m3
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3
Low boiling point naphtha - unspecified	Workers	Inhalation	Long-term systemic effects	608 mg/m3
xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	83 mg/m3
	Workers	Inhalation	Long-term local effects	83 mg/m3
ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
isopropanol	Workers	Inhalation	Long-term systemic effects	500 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Material	:	Solvent-resistant gloves
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	:	In the case of vapour formation use a respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid, viscous
Colour	:	orange
Odour	:	characteristic
pH	:	Not applicable
Melting point/range	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	29 °C Method: ISO 1523, closed cup Setaflash
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	not determined
Density	:	0.948 g/cm ³ (20 °C) Method: ISO 2811-1
Solubility(ies) Water solubility	:	not determined
Viscosity Viscosity, dynamic	:	192 mPa.s (20 °C) Method: ISO 2555
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C)

9.2 Other information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 10,768 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 17,600 mg/kg
Method: OECD Test Guideline 402

butan-1-ol:

Acute oral toxicity : LD50 Oral (Rat): 790 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 24.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg
Method: OECD Test Guideline 402

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 Oral (Rat): 3,592 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,160 mg/kg
Method: OECD Test Guideline 402

xylene (mixture of isomers):

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 22.08 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Converted acute toxicity point estimate

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 17.4 mg/l
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Method: OECD Test Guideline 402

isopropyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 5,045 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 10000 ppm
Exposure time: 6 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Result: Skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye damage.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Germ cell mutagenicity - Assessment : Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Carcinogenicity - Assessment : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-butyl acetate:

- | | |
|---|--|
| Toxicity to fish | : LC50 (Fish): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia (water flea)): 32 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Algae): 675 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

butan-1-ol:

- | | |
|---|---|
| Toxicity to fish | : LC50 (Fish): 1,376 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia (water flea)): 1,328 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : EC50 (Algae): 500 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Solvent naphtha (petroleum), light arom.:

- Toxicity to fish : LC50 (Fish): 9.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3.2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Algae): 2.9 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

xylene (mixture of isomers):

- Toxicity to fish : LC50 (Fish): 14 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 16 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Algae): > 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ethylbenzene:

- Toxicity to fish : LC50 (Fish): 12 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1.8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Algae): 33 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

isopropyl alcohol:

- Toxicity to fish : LC50 (Fish): 9,640 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 13,300 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Algae): > 1,000 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Method: OECD Test Guideline 201

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : 1263
IMDG : UN 1263
IATA (Cargo) : UN 1263

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

ADR : PAINT
IMDG : PAINT
IATA (Cargo) : Paint

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA (Cargo) : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Labels : 3
IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no
IMDG
Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet	2,500 t	25,000 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

fuels), (c) gas oils
(including diesel fuels,
home heating oils and gas
oil blending streams),(d)
heavy fuel oils (e)
alternative fuels serving the
same purposes and with
similar properties as
regards flammability and
environmental hazards as
the products referred to in
points (a) to (d)

15.2 Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

SECTION 16: Other information

Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H228	: Flammable solid.
H261	: In contact with water releases flammable gases.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Flam. Sol.	: Flammable solids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
Water-react.	: Substances and mixtures, which in contact with water, emit flammable gases

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : <http://echa.europa.eu>, <http://eur-lex.europa.eu>

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DICROM DP-902

Version
1.0

Revision Date:
05.07.2018

SDS Number:
H55821

Aquatic Chronic 3

H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN